

# JT 2127/FLEX SOCKETS

Adapter to connect a PCB-mounted DIMM & SODIMM socket to JT 2127/DMU



- ✓ **Test DIMM sockets thoroughly**
- ✓ **Easily connect JT 2127/DMU to DIMM sockets**
- ✓ **Compatible with DIMM sockets**
- ✓ **Built-in**

JT 2127/Flex is a family of hardware adapters specifically designed for the testing of a variety of PCB-mounted DIMM & SODIMM sockets (sizes and styles) using a JTAG/boundary-scan controller and supporting software.

## Long-standing challenge

The problem of testing memory sockets has always been troublesome for test and production engineers using JTAG/boundary-scan systems. Even when it is possible to create memory writes/reads from a boundary-scan compliant access device on the UUT (Unit Under Test), the initialization process may fail leaving you with little diagnostics information. What's more it can still be uncertain whether a fault lays with the DIMM module itself or the socket. Using the JT 2127/Flex system from JTAG Technologies you get pin-point diagnostics from a known-good test interface so you can be certain if your socket is soldered correctly.

## Global Representation

Want to know more about our solutions and products?  
Please contact us at our head office or visit our contact page.

### JTAG Technologies (Headquarters)

Boschdijk 50, 5612 AN Eindhoven, The Netherlands  
+31 (0)40 295 0870  
[info@jtag.com](mailto:info@jtag.com)  
[www.jtag.com](http://www.jtag.com)

## Modular System

The JT 2127/Flex system comprises two basic elements. A) a high-speed multi-channel IO module – JT 2127/DMU, and B) a personality adapter for the chosen DIMM type – JT 2127/Flex xxx. The combination of the DMU and Flex adapter allows test signals to be sent to and from the boundary-scan source device on the UUT performing a thorough check for open pins and short circuits.

In addition the voltages on the power pins of the DIMM socket are also measured. Currently supported DIMM types are xxx = 204-3, 244-mi3, 260-4 & 288-4. Due to the modularity of this test system other DIMM formats can be supported quickly upon request.

## Software

Software support for test development is provided through JTAG Technologies *ProVision* developer tool suite which is shipped with a full set of support files for the new system. Completed DIMM socket test applications will also run on the full range of PIP runtime software modules and symphony systems where appropriate.


## Easy connection

Supplied ribbon cables allow simple connection from the DMU master to the individual test adapters which themselves are equipped with flex-connect interfaces, making it easy to plug into most DIMM socket topographies.

## Analog Measurements

The JT 2127-Flex system is equipped with analog measurement channels as well as Digital IO (continuity test) channels in order to verify socket supply voltages. These analog channels connect through to the socket using the same flexible personality connector as the digital lines.

Use the QR code for an overview of our global offices and local representatives:  
[www.jtag.com/contact-us](http://www.jtag.com/contact-us)



We *are* boundary-scan.®